


## भाकुअनुप-राष्ट्रीय पशुरोग जानपदिक एवं सूचना विज्ञान संस्थान ICAR-National Institute of Veterinary Epidemiology and Disease Informatics रामगोंडनहल्ली, येलहंका, बेंगलुरू - 560064





Dated: 10.11.2023

F.No.10-31/NIVEDI/2015-16

## **CORRINGENDUM**

Ref: NOTICE INVITING ONLINE TENDER no. F.No.10-31/NIVEDI/2015-16 Dated: 04.11.2023 for External Repainting of Training cum Farmers' hostel ICAR-**NIVEDI Bangalore** published the CPP Portal website in http://eprocure.gov.in/eprocure/app vide tender ID No. 2023 DARE 779613 1 dated 04.11.2023.

Tenderers are requested to provide the split up of price quoted for the above tender in the technical bid in the following format.

SI. No.	Details	Unit	Qty.	Rate in Rs. Per Sqm	Total in Rs.
	External repainting				
1	Removing white or colour wash and epoxy paint by scrapping and sand papering and preparing the surface smooth including necessary repairsto scratches etc. complete	Sqm	100		
2	Finishing walls with Acrylic Smooth exterior paint of required shade Oldwork (One or more coat applied @ 0.90 ltr/10 sqm).for window chajja and sills (Asian Tractor / Jonson Nicholson /Berger/Nerolac)	Sqm	4,000		
3	Providing plastering 12 mm cement plaster of mix : 1:6 (1cement: 6 finesand)	Sqm	05		
4	Applying one coat of water thinnable cement primer of (Asian TractorPremium / Jenson Nicholson ) on wall surface Water thinnable cement primer	Sqm	05		
5	Providing and applying white cement-based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete (Birla and equivalent)	Sqm	05		
	Internal Repainting for entrance lobby and stair case head roomonly				

7	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surfacesmoothincluding necessary repairs to	Sqm	50	
8	Applying one coat of water thinnable cement primer of approved brandand manufacture on wall surface Water thinnable cement primer	Sqm	50	
9	Providing and applying white cement-based putty of average thickness1 mm, of approved brand and manufacturer, over the plastered wall	Sqm	50	

Sd/-

Administrative Officer